GlassProtect

Wireless glass break detector

The detector uses an electret microphone to recognize low-frequency hit sounds and high-frequency crashing sounds of glass shatters. The two-step glass break detection decreases the likelihood of false alarms.

Maximum Performance

- Communicates at a distance of up to 1,000 m from the hub

- Detects glass breaking at a distance of up to 9 m

- Delivers an alarm signal within 0.15 s

- Operates up to 7 years on the pre-installed battery

- Features an external contact for connecting third-party detectors

Effortless Operation

- 3 adjustable sensitivity levels

- Two-factor glass break detection to register high- and low-pitched sounds

- Two-way communication with the hub for testing and configuring

Simple Installation

- Use the QR code to connect the device to the hub

- Use the SmartBracket to mount the device without disassembling it

- Open the app to test connection quality and configure device settings

Bulletproof Protection

- Tampering alarm

- Data encryption

- Device forgery prevention

Ajax Systems

EVERSMART®

Tech Specs

- Color: white/black

- Installation: indoors

- Radio communication range: up to 1,000 m

- Compatibility: all hubs & ReX

- Sensing element: electret microphone

- Microphone coverage angle: 180°

- Glass break detection distance: up to 9 m

- Temperature sensor: available

- Battery: CR123A, pre-installed

- Battery life: up to 7 years

- Protection class: IP50

- Operating temperature range: from +5°C to +40°C

- Permissible humidity: up to 75%

- Dimensions:
  Diameter — 20 mm
  Height — 90 mm

- Weight: 30 g

Ajax Systems