



# Transmitter




## Module for third-party detector integration

Wireless module for connecting third-party detectors (i.e. IR barriers, liquid level detectors, gas detectors, and thermal relays) to the Ajax security system.




### Maximum Performance

- Communicates at a distance of up to 1,600 m from the hub
- Compatible with detectors featuring NC/NO outputs
- Delivers an alarm signal within 0.15 s
- Operates up to 5 years on the pre-installed batteries
- Provides 3.3 V power supply for connected device

### Simple Installation

-  Use the QR code to connect the device to the hub
-  Open the app to test connection quality and configure device settings
-  Install the device into the detector's body or a mounting box

### Bulletproof Protection

-  Tampering and accelerometer alarm
-  Data encryption
-  Device forgery prevention

### Effortless Operation

- Suitable for indoor and outdoor operation
- Indicates battery level in the app
- Two-way communication with the hub for testing and configuring

## Tech Specs

- Installation: indoors/outdoors
- Compatibility: all hubs & ReX
- Radio communication range: up to 1,600 m
- Alarm input: 1
- Tamper input: 1
- Battery: 3x CR123A batteries, pre-installed
- Detector contact type: NO/NC
- Terminals: power supply (+/-), alarm, tamper
- Power supply output: 3.3 V
- Battery life: up to 5 years
- Operating temperature range: from -25°C to +50°C
- Permissible humidity: up to 75%
- Dimensions: 100x39x22 mm
- Weight: 74 g



Ajax Systems

**EVERSMART**